

Options and Accessories



Lighting Package*



Plastic Canopy Top



Custom Van Box



Rear Cargo Cage



Electric Bed Lift




Underhood Storage
(Gas Only)



Stake-Side Kit



2-Inch Front
Receiver Hitch



Cargo Bed Toolbox



2,500 lb Warn Winch



Pintle Hitch



Cab Heater



Nerf Bars



54- or 62-Inch
Plow Blade



60-Inch finish
cut mower



Swisher Dump Cart



50-Gallon Sprayer



Front Steel
Skid Plate



Roof-mounted
Strobe Light



5-Panel Mirror

*Includes horn, turn signals and brakelights

Club Car

CARRYALL 295

UTILITY VEHICLE



Ingersoll Rand is a world leader in the field of compact vehicles and equipment. Our widely known Bobcat® brand includes an extensive line of powerful, nimble compact construction equipment and attachments, and our state-of-the-art engineering capabilities and stylish designs are reflected in our world famous Club Car® vehicles.

1.800.CLUBCAR • +1 706.863.3000

www.clubcar.com www.ingersollrand.com



CARRYALL 295


Look no further for the industry's first fully automatic 4x4 utility vehicle. Club Car's revolutionary IntelliTrak™ 4-wheel-drive system constantly senses the driving environment and instantly engages and disengages 4-wheel-drive operation as the surroundings change. With nothing to engage, shift or lock, you get a 4x4 that's easy for your whole team to drive. With unique comfort features and durable construction, the Carryall 295 means serious business anywhere you put it to work.

Features

IntelliTrak™:
An automatic full-time,
All-Wheel-Drive system



23 hp air-cooled Kawasaki®
gas or 20 hp liquid-cooled
Kubota® diesel engine



Standard Color:
Dark Gray



Optional Color:
Green



Rustproof, non-corrosive,
box tube 6061 aircraft-grade
aluminum frame, chassis
and cargo box



Roll Over Protective
Structure certified
to meet 5 different
international
standards



15.1 ft³ (0.4 m³)
Cargo Box carries
800 lb (362.9 kg)



Four-wheel,
hydraulic
disc brakes



Double A-Arm
front suspension
w/coil-over shocks

Additional Features

- **Maximum speed of 25 mph (40.2 kph)**
- **1,200 lb (544.3 kg) total vehicle capacity; High Capacity option: 1,450 lb (657.7 kg)**
- **Maximum hp @ 3,600 rpm exceeds SAE J1940/1349 Performance Standards**
- **12.1 in (30.7 cm) ground clearance under foot platform to handle rough terrain**
- **25" heavy-duty, all-terrain tire standard; 25" heavy-duty, mud tire optional**

Specifications

| | Carryall 295 Gasoline | Carryall 295 Diesel | |
|---------------------------------|---|--|---|
| POWER SUPPLY | Engine | Kawasaki, 675 cc, 2-cylinder, industrial grade | Kubota D722, 719 cc, 3-cylinder |
| | Engine – Cooling | Air | Liquid |
| | Engine – Lubrication & Oil Filter Type | Full-pressure spin-on | Full-pressure spin-on |
| | Max Torque | 39.8 ft-lb (54 Nm) | 33 ft-lb (44.7 Nm) |
| | Horsepower | 23 (17.2 kw) @ 3,600 rpm per SAE J1940/1349 | 20 (14.9 kw) |
| | Ignition | Transistorized magneto | Compression |
| | 4WD Engagement | Automatic – IntelliTrak | Automatic – IntelliTrak |
| | Differential – Front | Automatic – IntelliTrak | Automatic – IntelliTrak |
| | Differential – Rear | Auto locking – IntelliTrak | Auto locking – IntelliTrak |
| | Electrical System | 12-volt, 500 CCA | 12-volt, 500 CCA |
| Torque Converter | CVT | CVT | |
| STEERING/ SUSPENSION | Steering Type | Rack & pinion | Rack & pinion |
| | Tilt Steering Wheel | Standard | Standard |
| | Adjustable Driver's Seat | Only available with bucket seat option | Only available with bucket seat option |
| | Suspension – Front | Independent double A-arms w/coil-over shocks | Independent double A-arms w/coil-over shocks |
| | Suspension – Rear | Swing arm w/coil-over shocks | Swing arm w/coil-over shocks |
| | Brakes | Four-wheel, hydraulic disc | Four-wheel, hydraulic disc |
| | Park Brake | Automotive style | Automotive style |
| FRAME/CHASSIS | Frame/Chassis | Tubular aluminum | Tubular aluminum |
| | Body – Front | GE Geloy High-impact, scratch-resistant, injection molded color | GE Geloy High-impact, scratch-resistant, injection molded color |
| | Body – Rear | All aluminum cargo bed | All aluminum cargo bed |
| | Tires – Front | All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional) | All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional) |
| | Tires – Rear | All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional) | All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional) |
| | Instrumentation | Electronic fuel gauge/hour meter, low oil warning light (speedometer optional) | Electronic fuel gauge/hour meter, low oil warning light, coolant high temp warning light (speedometer optional) |
| DIMENSIONS | Bed Length x Width x Height | 48.8" x 49.8" x 10.9" (124 cm x 126.5 cm x 27.7 cm) | 48.8" x 49.8" x 10.9" (124 cm x 126.5 cm x 27.7 cm) |
| | Overall Bed Height | 33" (83.8 cm) | 33" (83.8 cm) |
| | Bed Load Capacity | 800 lb (362.9 kg)* | 800 lb (362.9 kg)* |
| | Total Vehicle Capacity | 1,200 lb (544.3 kg)** | 1,200 lb (544.3 kg)** |
| | Fuel Tank Capacity | 6.5 gal (24.6 L) | 6.5 gal (24.6 L) |
| | Overall Length x Width x Height | 124.6" x 60" x 78.6" (316.5 cm x 152.4 cm x 199.6 cm) | 124.6" x 60" x 78.6" (316.5 cm x 152.4 cm x 199.6 cm) |
| | Wheelbase | 88.7" (225.3 cm) | 88.7" (225.3 cm) |
| | Ground Clearance – Differential | 7.4" (18.8 cm) | 7.4" (18.8 cm) |
| | Tread Centers (Front/Rear) | 48.8" (124 cm) front and rear | 48.8" (124 cm) front and rear |
| | Dry Weight (Less Batteries) | 1,339 lb (599 kg) | 1,475 lb (669.1 kg) |
| | Maximum Speed | 25 mph (40.2 kph) | 25 mph (40.2 kph) |
| | Turning Radius | 11.5 ft (3.5 m) | 11.5 ft (3.5 m) |
| | Vehicle Warranty | 2-year/2,000-hour, limited | 2-year/2,000-hour, limited |

*1,050 lb (476.3 kg) available
**1,450 lb (657.7 kg) available

