

Options and Accessories



Lighting Package*



Plastic Canopy Top



Custom Van Box



Rear Cargo Cage



Electric Bed Lift



Underhood Storage
(Gas Only)



Stake-Side Kit



2-Inch Front
Receiver Hitch



Cargo Bed Toolbox



2,500 lb Warn Winch



Pintle Hitch



Cab Heater



Nerf Bars



54- or 62-Inch
Plow Blade



60-Inch finish
cut mower



Swisher Dump Cart



50-Gallon Sprayer



Front Steel
Skid Plate



Roof-mounted
Strobe Light



5-Panel Mirror

*Includes horn, turn signals and brakelights

Club Car

CARRYALL 295SE

UTILITY VEHICLE



Ingersoll Rand is a world leader in the field of compact vehicles and equipment. Our widely known Bobcat® brand includes an extensive line of powerful, nimble compact construction equipment and attachments, and our state-of-the-art engineering capabilities and stylish designs are reflected in our world famous Club Car® vehicles.

1.800.CLUBCAR • +1 706.863.3000

www.clubcar.com www.ingersollrand.com



CARRYALL 295 SE


The Carryall 295 SE offers seating for 3 passengers and a driver. Now you can transport more people as well as have an ample amount of cargo space for hauling supplies — helping you and your crew get the job done. The Carryall 295 SE comes with the IntelliTrak™ All-Wheel-Drive system. So now you won't have to worry about shifting into 4-wheel drive when the environment gets rough. This utility vehicle does it for you automatically by sensing the ground you're on. No matter where your work takes you and your crew, the Carryall 295 SE can get all of you there.

Features

IntelliTrak™:
An automatic full-time,
All-Wheel-Drive system



23 hp air-cooled Kawasaki®
gas or 20 hp liquid-cooled
Kubota® diesel engine



Standard Color:
Dark Gray



Optional Color:
Green



Rustproof, non-corrosive,
box tube 6061 aircraft-grade
aluminum frame, chassis
and cargo box



Roll Over Protective
Structure certified
to meet 5 different
international
standards



4-forward facing
seats, your choice
in each row
— buckets or bench



15.1 ft³ (0.4 m³)
Cargo Box carries
800 lb (362.9 kg)



Four-wheel,
hydraulic
disc brakes



Double A-Arm
front suspension
w/coil-over shocks

Additional Features

- Maximum speed of 25 mph (40.2 kph)
- 1,600 lb (725.7 kg) total vehicle capacity
- Maximum hp @ 3,600 rpm exceeds SAE J1940 Performance Standards
- 25" heavy-duty, all-terrain tire standard; 25" heavy-duty, mud tire optional
- 12.1 in (30.7 cm) ground clearance under foot platform to handle rough terrain

Specifications

	Carryall 295 SE Gasoline	Carryall 295 SE Diesel	
POWER SUPPLY	Engine	Kawasaki, 675 cc, 2-cylinder, industrial grade	Kubota D722, 719 cc, 3-cylinder
	Engine – Cooling	Air	Liquid
	Engine – Lubrication & Oil Filter Type	Full-pressure spin-on	Full-pressure spin-on
	Max Torque	39.8 ft-lb (54 Nm)	33 ft-lb (44.7 Nm)
	Horsepower	23 (17.2 kw) @ 3,600 rpm per SAE J1940/1349	20 (14.9 kw)
	Ignition	Transistorized magneto	Compression
	4WD Engagement	Automatic – IntelliTrak	Automatic – IntelliTrak
	Differential – Front	Automatic – IntelliTrak	Automatic – IntelliTrak
	Differential – Rear	Auto locking – IntelliTrak	Auto locking – IntelliTrak
Electrical System	12-volt, 500 CCA	12-volt, 500 CCA	
Torque Converter	CVT	CVT	
STEERING/ SUSPENSION	Steering Type	Rack & pinion	Rack & pinion
	Tilt Steering Wheel	Standard	Standard
	Adjustable Driver's Seat	Only available with bucket seat option	Only available with bucket seat option
	Suspension – Front	Independent double A-arms w/coil-over shocks	Independent double A-arms w/coil-over shocks
	Suspension – Rear	Swing arm w/coil-over shocks	Swing arm w/coil-over shocks
	Brakes	Four-wheel, hydraulic disc	Four-wheel, hydraulic disc
Park Brake	Automotive style	Automotive style	
FRAME/CHASSIS	Frame/Chassis	Tubular aluminum	Tubular aluminum
	Body – Front	GE Geloy High-impact, scratch-resistant, injection molded color	GE Geloy High-impact, scratch-resistant, injection molded color
	Body – Rear	All aluminum cargo bed	All aluminum cargo bed
	Tires – Front	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)
	Tires – Rear	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)
	Instrumentation	Electronic fuel gauge/hour meter, low oil warning light (speedometer optional)	Electronic fuel gauge/hour meter, low oil warning light, coolant high temp warning light (speedometer optional)
DIMENSIONS	Bed Length x Width x Height	48.8" x 49.8" x 10.9" (124 cm x 126.5 cm x 27.7 cm)	48.8" x 49.8" x 10.9" (124 cm x 126.5 cm x 27.7 cm)
	Overall Bed Height	33" (83.8 cm)	33" (83.8 cm)
	Bed Load Capacity	800 lb (362.9 kg)	800 lb (362.9 kg)
	Total Vehicle Capacity	1,600 lb (725.7 kg)	1,600 lb (725.7 kg)
	Fuel Tank Capacity	6.5 gal (24.6 L)	6.5 gal (24.6 L)
	Overall Length x Width x Height	157.6" x 60" x 78.6" (400.3 cm x 152.4 cm x 199.6 cm)	157.6" x 60" x 78.6" (400.3 cm x 152.4 cm x 199.6 cm)
	Wheelbase	114" (289.6 cm)	114" (289.6 cm)
	Ground Clearance – Differential	7.4" (18.8 cm)	7.4" (18.8 cm)
	Tread Centers (Front/Rear)	48.8" (124 cm) front and rear	48.8" (124 cm) front and rear
	Dry Weight (Less Batteries)	1,605 lb (728 kg)	1,786 lb (810.1 kg)
	Maximum Speed	25 mph (40.2 kph)	25 mph (40.2 kph)
	Turning Radius	17.0 ft (5.2 m)	17.0 ft (5.2 m)
	Vehicle Warranty	2-year/2,000-hour, limited	2-year/2,000-hour, limited

